

Transforming Architecture LLC 7612 Browns Bridge Road Highland, Maryland 20777 p. 301-776-2666 f. 301-776-2886 1-877-828-7267

www.TransformingArchitecture.com info@TransformingArchitecture.com

ACCESSIBLE PLACE HOME EVALUATION CHECKLIST

lient Name:
ddress:
hone:
ate:
xterior
 Low-maintenance exterior (vinyl, brick) Low-maintenance shrubs and plants Deck, patio, or balcony surfaces are no more than ½ inch below interior floor level if made of wood
NOTES:
verall Floor Plan
 Main living on a single story, including full bath No steps between rooms/areas on the same level 5-foot by 5-foot clear/turn space in living area, kitchen, a bedroom, and a bathroom NOTES:
NOTEO.
allways
□ Minimum of 36 inches wide, wider preferred□ Well lit
NOTES:

Entry				
	At least one no-step entry with a cover Sensor light at exterior no-step entry focusing on the front-door lock There needs to be 32 inches of clear width, which requires a 36-inch door Non-slip flooring in foyer Entry door sidelight or high/low peep hole viewer; sidelight should provide both privacy and safety Doorbell in accessible location			
NC	TES:			
Thresh	nolds			
	Flush preferable Exterior maximum of ½ inch beveled Interior maximum of ¼ inch			
NC	TES:			
Interio	r Doors			
	There needs to be 32 inches of clear width, which requires a 36-inch door Levered door hardware			
NC)TES:			
Windo	ws			
	Plenty of windows for natural light Lowered windows or taller windows with lower sill height Low maintenance exterior and interior finishes Easy to operate hardware			
NC	TES:			
Garage	e or Carport			
	Covered carports and boarding spaces Wider than average carports to accommodate lifts on vans			

	 □ Five-foot minimum access aisle between accessible van and car in garage □ If code requires floor to be several inches below entrance to house for fume protection, can slope entire floor from front to back to eliminate need for ramp or step □ Ramp to doorway if needed 			
NO	DTES:			
Fauce	ts			
	Lever handles or pedal-controlled			
	Thermostatic or anti-scald controls			
	Pressure balanced faucets			
NO	DTES:			
Kitchen and Laundry				
Count	rers			
	Wall support and provision for adjustable and/or varied height counters and removable base			
	cabinets			
	Upper wall cabinetry three inches lower than conventional height			
	Accented stripes on edge of countertops to provide visual orientation to the workspace			
	Counter space for dish landing adjacent to or opposite all appliances			
	Base cabinet with roll out trays and lazy susans			
	Pull-down shelving			
	Glass-front cabinet doors			
	Open shelving for easy access to frequently used items			
NO	OTES:			
Applia	ances			
	Easy to read controls			
	Washing machine and dryer raised 12 to 15 inches above floor			
	Front loading laundry machines			
	Microwave oven at counter height or in wall			
	Side-by-side refrigerator/freezer			
	Side-swing or wall oven			
	Raised dishwasher with pushbutton controls			
	Electric cook top with level burners for safety in transferring between the burners, front controls			
	and downdraft feature to pull heat away from user; light to indicate when surface is hot			

Transf	forming Architecture LLC	_ Evaluation			
NC	OTES:				
Misce	llaneous				
	 Multi-level work areas to accommodate cooks of different heights Open under-counter seated work areas Placement of task lighting in appropriate work areas Loop handles for easy grip and pull Pull-out spray faucet; levered handles 				
NC	DTES:				
Bathro	oom				
	Wall support and provision for adjustable and/or varied height counters and removal cabinets	ole base			
	Contrasting color edge border at countertops At least one wheelchair maneuverable bath on main level with 60-inch turning radius acceptable T-turn space and 36-inch by 36-inch or 30-inch by 48-inch clear space Bracing in walls around tub, shower, shower seat, and toilet for installation of grab b 250 - 300 pounds If stand-up shower is used in main bath, it is curbless and minimum of 36 inches wid Bathtub - lower for easier access Fold down seat in the shower Adjustable/ handheld showerheads, 6-foot hose Tub/Shower controls offset from center Shower stall with built-in antibacterial protection Light in shower stall Toilet 2 ½ inches higher than standard toilet (17 to 19 inches) or height-adjustable Design of the toilet paper holder allows rolls to be changed with one hand Wall-hung sink with knee space and panel to protect user from pipes Slip-resistant flooring in bathroom and shower	ars to support			
	OTES:				
Stairw	vays, Lifts, and Elevators				
	Adequate hand rails on both sides of stairway, 1 ¼-inch diameter Increased visibility of stairs through contrast strip on top and bottom stairs, color contreads and risers on stairs and use of lighting	itrast between			

	Multi-story homes may provide either pre-framed shaft (ie. stacked closets) for future elevator, or				
	stairway width must be minimum of 4 feet to allow space for lift				
	□ Residential elevator or lift				
N	IOTES:				
Ramp	os				
_					
	Slope no greater than one inch rise for each 12 inches in length, adequate handrails				
	The second secon				
	Two-inch curbs for safety				
N	OTES:				
Stora	age				
	Adjustable closet rods and shelves				
	Lighting in closets				
	Easy open doors that do not obstruct access				
Ν	IOTES:				
Elect	rical, Lighting, Safety, and Security				
	g ,				
	9				
	3				
	higher than 48 inches from floor Electrical outlets 15 inches on center from floor; may need to be closer than 12 feet apart				
	CO ₂ detectors have been activated				
	lighting, from any TV in the house				
	,				
	P				
	- ()				
	· · · · · · · · · · · · · · · · · · ·				
	Home wired for computers				
Ν	IOTES:				

Flooring			
1 100111	ig		
	Smooth, non-glare, slip-resistant surfaces, interior and exterior		
	If carpeted, use low (less than ½ inch high pile) density, with firm pad		
	Color/texture contrast to indicate change in surface levels		
NC	DTES:		
Heatin	g, Ventilation, and Air Conditioning		
	HVAC should be designed so filters are easily accessible		
	Energy-efficient units		
	Windows that can be opened for cross ventilation, fresh air		
NC	DTES:		
Energy	y-Efficient Features		
	In-line framing with two by six studs spaced 24-inch on center		
	Air-barrier installation and sealing of duct work with mastic		
	Reduced-size air conditioning units with gas furnaces		
	Mechanical fresh air ventilation, installation of air returns in all bedrooms and use of carbon		
	monoxide detectors		
	Installation of energy efficient windows with Low-E glass		
NC	DTES:		
Reduc	ed Maintenance/Convenience Features		
П	Easy to clean surfaces		
	Central vacuum		
	Built-in pet feeding system		
	Built-in recycling system		
	Video phones		
	Intercom system		
NC	DTES:		
Other Ideas			
	Separate apartment for rental income or future caregiver		
	Flex room that can used as a nursery or playroom when the children are young and as a home office later; if combined with a full bath, room could also be used for an aging parent/aging in place		

Transforming Architecture LLC	Evaluation
NOTES:	
Recommendations (other than noted in list above):	
Exterior:	
Overall Floor Plan:	
Entry(Interior):	
Kitchen & Laundry:	
Miscellaneous:	
Bathroom:	
Stairways, Lifts, Elevators:	
Electrical:	
Flooring:	
Other ideas:	